

54AC16620, 74AC16620 16-BIT BUS TRANSCEIVERS WITH 3-STATE OUTPUTS

SCAS239A – JULY 1990 – REVISED APRIL 1996

- **Members of the Texas Instruments Widebus™ Family**
- **3-State Outputs Drive Bus Lines Directly**
- **Flow-Through Architecture Optimizes PCB Layout**
- **Distributed V_{CC} and GND Pin Configurations Minimize High-Speed Switching Noise**
- **EPIC™ (Enhanced-Performance Implanted CMOS) 1-μm Process**
- **500-mA Typical Latch-Up Immunity at 125°C**
- **Package Options Include Plastic 300-mil Shrink Small-Outline (DL) Packages Using 25-mil Center-to-Center Pin Spacings and 380-mil Fine-Pitch Ceramic Flat (WD) Packages Using 25-mil Center-to-Center Pin Spacings**

description

The 'AC16620 are inverting 16-bit transceivers designed for asynchronous communication between data buses. The control-function implementation allows for maximum flexibility in timing.


These devices can be used as two 8-bit transceivers or one 16-bit transceiver. They allow data transmission from the A bus to the B bus or from the B bus to the A bus, depending on the logic level at the complementary output-enable (OEAB or OEBA) inputs. The output-enable inputs can be used to disable the device so that the buses are effectively isolated.

The dual-enable configuration gives the transceiver the capability to store data by simultaneously enabling OEAB and OEBA. Each output reinforces its input in this transceiver configuration. Thus, when both control inputs are enabled and all other data sources to the two sets of bus lines are at high impedance, the bus lines remain at their last states.

The 74AC16620 is packaged in TI's shrink small-outline package, which provides twice the I/O pin count and functionality of standard small-outline packages in the same printed-circuit-board area.

The 54AC16620 is characterized for operation over the full military temperature range of –55°C to 125°C. The 74AC16620 is characterized for operation from –40°C to 85°C.

54AC16620 . . . WD PACKAGE
74AC16620 . . . DL PACKAGE
(TOP VIEW)



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

EPIC and Widebus are trademarks of Texas Instruments Incorporated.

UNLESS OTHERWISE NOTED this document contains PRODUCTION DATA information current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

**TEXAS
INSTRUMENTS**


POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 1996, Texas Instruments Incorporated

FUNCTION TABLE
(each 8-bit section)



INPUTS		OPERATION
OEBA	OEAB	
L	L	\overline{B} data to A bus
L	H	\overline{B} data to A bus, A data to B bus
H	L	Isolation
H	H	\overline{A} data to B bus

logic symbol†



† This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

logic diagram (positive logic)



absolute maximum ratings over operating free-air temperature range (unless otherwise noted)†

Supply voltage range, V_{CC}	–0.5 V to 7 V
Input voltage range, V_I (see Note 1)	–0.5 V to $V_{CC} + 0.5$ V
Output voltage range, V_O (see Note 1)	–0.5 V to $V_{CC} + 0.5$ V
Input clamp current, I_{IK} ($V_I < 0$ or $V_I > V_{CC}$)	±20 mA
Output clamp current, I_{OK} ($V_O < 0$ or $V_O > V_{CC}$)	±50 mA
Continuous output current, I_O ($V_O = 0$ to V_{CC})	±50 mA
Continuous current through V_{CC} or GND	±400 mA
Maximum power dissipation at $T_A = 55^\circ\text{C}$ (in still air) (see Note 2): DL package	1.2 W
Storage temperature range, T_{stg}	–65°C to 150°C

† Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

- NOTES: 1. The input and output voltage ratings may be exceeded if the input and output current ratings are observed.
2. The maximum package power dissipation is calculated using a junction temperature of 150°C and a board trace length of 750 mils.

54AC16620, 74AC16620

16-BIT BUS TRANSCEIVERS

WITH 3-STATE OUTPUTS

SCAS239A – JULY 1990 – REVISED APRIL 1996

recommended operating conditions (see Note 2)

			54AC16620			74AC16620			UNIT
			MIN	NOM	MAX	MIN	NOM	MAX	
V _{CC}	Supply voltage		3	5	5.5	3	5	5.5	V
V _{IH}	High-level input voltage	V _{CC} = 3 V	2.1			2.1			V
		V _{CC} = 4.5 V	3.15			3.15			
		V _{CC} = 5.5 V	3.85			3.85			
V _{IL}	Low-level input voltage	V _{CC} = 3 V			0.9			0.9	V
		V _{CC} = 4.5 V			1.35			1.35	
		V _{CC} = 5.5 V			1.65			1.65	
V _I	Input voltage		0		V _{CC}	0		V _{CC}	V
V _O	Output voltage		0		V _{CC}	0		V _{CC}	V
I _{OH}	High-level output current	V _{CC} = 3 V			–4			–4	mA
		V _{CC} = 4.5 V			–24			–24	
		V _{CC} = 5.5 V			–24			–24	
I _{OL}	Low-level output current	V _{CC} = 3 V			12			12	mA
		V _{CC} = 4.5 V			24			24	
		V _{CC} = 5.5 V			24			24	
Δt/Δv	Input transition rise or fall rate		0		10	0		10	ns/V
T _A	Operating free-air temperature		–55		125	–40		85	°C

NOTE 3: Unused inputs must be held high or low to prevent them from floating.

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER		TEST CONDITIONS	V _{CC}	T _A = 25°C			54AC16620		74AC16620		UNIT
				MIN	TYP	MAX	MIN	MAX	MIN	MAX	
V _{OH}	I _{OH} = –50 μA		3 V	2.9			2.9		2.9		V
			4.5 V	4.4			4.4		4.4		
			5.5 V	5.4			5.4		5.4		
	I _{OH} = –4 mA		3 V	2.58			2.48		2.48		
			4.5 V	3.94			3.8		3.8		
			5.5 V	4.94			4.8		4.8		
V _{OL}	I _{OL} = 50 μA		3 V			0.1		0.1		0.1	V
			4.5 V			0.1		0.1		0.1	
			5.5 V			0.1		0.1		0.1	
	I _{OL} = 12 mA		3 V			0.36		0.44		0.44	
			4.5 V			0.36		0.44		0.44	
			5.5 V			0.36		0.44		0.44	
I _I	Control inputs	V _I = V _{CC} or GND	3 V								μA
			4.5 V								
			5.5 V								
	A or B ports	V _O = V _{CC} or GND	3 V								
			4.5 V								
			5.5 V								
I _{CC}		V _I = V _{CC} or GND, I _O = 0	5.5 V			8		80		80	μA
C _i	Control inputs	V _I = V _{CC} or GND	5 V			4.5					pF
C _{io}	A or B ports	V _O = V _{CC} or GND	5 V			16					pF

† Not more than one output should be tested at a time, and the duration of the test should not exceed 10 ms.

‡ For I/O ports, the parameter I_{OZ} includes the input leakage current.

PRODUCT PREVIEW information concerns products in the formative or design phase of development. Characteristic data and other specifications are design goals. Texas Instruments reserves the right to change or discontinue these products without notice.



switching characteristics over recommended operating free-air temperature range,
 $V_{CC} = 3.3\text{ V} \pm 0.3\text{ V}$ (unless otherwise noted) (see Figure 1)


PARAMETER	FROM (INPUT)	TO (OUTPUT)	$T_A = 25^\circ\text{C}$			54AC16620		74AC16620		UNIT
			MIN	TYP	MAX	MIN	MAX	MIN	MAX	
t_{PLH}	A or B	B or A	2.7	6.1	8.7	2.7	9.7	2.7	9.7	ns
t_{PHL}			3.9	7.9	10.6	3.9	11.7	3.9	11.7	
t_{PZH}	\overline{OEBA}	A	3.2	7.1	10	3.2	11.2	3.2	11.2	ns
t_{PZL}			4.5	11.1	13.5	4.5	15	4.5	15	
t_{PHZ}	\overline{OEBA}	A	5.3	7.4	9.5	5.3	10.2	5.3	10.2	ns
t_{PLZ}			4.6	7	9.2	4.6	9.8	4.6	9.8	
t_{PZH}	OEAB	B	3.1	6.7	9.5	3.1	10.7	3.1	10.7	ns
t_{PZL}			4.4	9.6	13	4.4	14.5	4.4	14.5	
t_{PHZ}	OEAB	B	5	7.1	9.3	5	9.8	5	9.8	ns
t_{PLZ}			4.4	6.8	8.9	4.4	9.4	4.4	9.4	

switching characteristics over recommended operating free-air temperature range,
 $V_{CC} = 5\text{ V} \pm 0.5\text{ V}$ (unless otherwise noted) (see Figure 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	$T_A = 25^\circ\text{C}$			54AC16620		74AC16620		UNIT
			MIN	TYP	MAX	MIN	MAX	MIN	MAX	
t_{PLH}	A or B	B or A	2.1	3.9	6.1	2.1	6.8	2.1	6.8	ns
t_{PHL}			3.1	4.9	7.3	3.1	8.2	3.1	8.2	
t_{PZH}	\overline{OEBA}	A	2.2	4.3	6.8	2.2	7.6	2.2	7.6	ns
t_{PZL}			3.3	5.5	8.4	3.3	9.4	3.3	9.4	
t_{PHZ}	\overline{OEBA}	A	4.9	6.6	8.6	4.9	9.2	4.9	9.2	ns
t_{PLZ}			4.1	5.8	7.8	4.1	8.3	4.1	8.3	
t_{PZH}	OEAB	B	2.2	4.2	6.5	2.2	7.3	2.2	7.3	ns
t_{PZL}			3.4	5.4	8.1	3.4	9.1	3.4	9.1	
t_{PHZ}	OEAB	B	4.6	6.4	8.5	4.6	9	4.6	9	ns
t_{PLZ}			4.1	5.6	7.6	4.1	8	4.1	8	

operating characteristics, $V_{CC} = 5\text{ V}$, $T_A = 25^\circ\text{C}$

PARAMETER			TEST CONDITIONS		TYP	UNIT
C_{pd}	Power dissipation capacitance per transceiver	Outputs enabled	$C_L = 50\text{ pF}$, $f = 1\text{ MHz}$		49	pF
		Outputs disabled			6	



- NOTES:

A. C_L includes probe and jig capacitance.

B. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.

C. All input pulses are supplied by generators having the following characteristics: $PRR \leq 1\text{ MHz}$, $Z_O = 50\text{ }\Omega$, $t_r = 3\text{ ns}$, $t_f = 3\text{ ns}$.

D. The outputs are measured one at a time with one input transition per measurement.

Figure 1. Load Circuit and Voltage Waveforms

IMPORTANT NOTICE

Texas Instruments (TI) reserves the right to make changes to its products or to discontinue any semiconductor product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

TI warrants performance of its semiconductor products and related software to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

Certain applications using semiconductor products may involve potential risks of death, personal injury, or severe property or environmental damage ("Critical Applications").

TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, INTENDED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT APPLICATIONS, DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS.

Inclusion of TI products in such applications is understood to be fully at the risk of the customer. Use of TI products in such applications requires the written approval of an appropriate TI officer. Questions concerning potential risk applications should be directed to TI through a local SC sales office.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards should be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance, customer product design, software performance, or infringement of patents or services described herein. Nor does TI warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used.