

SN54ABT573A, SN74ABT573A OCTAL TRANSPARENT D-TYPE LATCHES WITH 3-STATE OUTPUTS

SCBS190B – JANUARY 1991 – MARCH 1996

- State-of-the-Art *EPIC-II^B*™ BiCMOS Design Significantly Reduces Power Dissipation
- ESD Protection Exceeds 2000 V Per MIL-STD-883C, Method 3015; Exceeds 200 V Using Machine Model (C = 200 pF, R = 0)
- Latch-Up Performance Exceeds 500 mA Per JEDEC Standard JESD-17
- Typical V_{OLP} (Output Ground Bounce) < 1 V at $V_{CC} = 5$ V, $T_A = 25^\circ\text{C}$
- High-Drive Outputs (–32-mA I_{OH} , 64-mA I_{OL})
- Package Options Include Plastic Small-Outline (DW) and Shrink Small-Outline (DB) Packages, Ceramic Chip Carriers (FK), and Plastic (N) and Ceramic (J) DIPs, and Ceramic Flat (W) Packages

description

These 8-bit latches feature 3-state outputs designed specifically for driving highly capacitive or relatively low-impedance loads. They are particularly suitable for implementing buffer registers, I/O ports, bidirectional bus drivers, and working registers.

The eight latches of the 'ABT573A are transparent D-type latches. While the latch-enable (LE) input is high, the Q outputs follow the data (D) inputs. When the latch enable is taken low, the Q outputs are latched at the logic levels set up at the D inputs.

A buffered output-enable (\overline{OE}) input can be used to place the eight outputs in either a normal logic state (high or low logic levels) or a high-impedance state. In the high-impedance state, the outputs neither load nor drive the bus lines significantly. The high-impedance state and increased drive provide the capability to drive bus lines without need for interface or pullup components.


\overline{OE} does not affect the internal operations of the latches. Old data can be retained or new data can be entered while the outputs are in the high-impedance state.

To ensure the high-impedance state during power up or power down, \overline{OE} should be tied to V_{CC} through a pullup resistor; the minimum value of the resistor is determined by the current-sinking capability of the driver.


The SN74ABT573A is available in TI's shrink small-outline package (DB), which provides the same I/O pin count and functionality of standard small-outline packages in less than half the printed circuit board area.

The SN54ABT573A is characterized for operation over the full military temperature range of -55°C to 125°C . The SN74ABT573A is characterized for operation from -40°C to 85°C .

SN54ABT573A . . . J OR W PACKAGE
SN74ABT573A . . . DB, DW, OR N PACKAGE
(TOP VIEW)



SN54ABT573A . . . FK PACKAGE
(TOP VIEW)



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

EPIC-II^B is a trademark of Texas Instruments Incorporated.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

**TEXAS
INSTRUMENTS**

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

Copyright © 1996, Texas Instruments Incorporated


SN54ABT573A, SN74ABT573A OCTAL TRANSPARENT D-TYPE LATCHES WITH 3-STATE OUTPUTS

SCBS190B – JANUARY 1991 – MARCH 1996


FUNCTION TABLE
(each latch)

| INPUTS | | | OUTPUT Q |
|------------------------|----|---|-------------|
| $\overline{\text{OE}}$ | LE | D | |
| L | H | H | H |
| L | H | L | L |
| L | L | X | Q_0 |
| H | X | X | Z |

logic symbol†



logic diagram (positive logic)



† This symbol is in accordance with ANSI/IEEE Std 91-1984 and IEC Publication 617-12.

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)‡

| | |
|---|-----------------|
| Supply voltage range, V_{CC} | –0.5 V to 7 V |
| Input voltage range, V_I (see Note 1) | –0.5 V to 7 V |
| Voltage range applied to any output in the high state or power-off state, V_O | –0.5 V to 5.5 V |
| Current into any output in the low state, I_O : SN54ABT573A | 96 mA |
| SN74ABT573A | 128 mA |
| Input clamp current, I_{IK} ($V_I < 0$) | –18 mA |
| Output clamp current, I_{OK} ($V_O < 0$) | –50 mA |
| Maximum power dissipation at $T_A = 55^{\circ}\text{C}$ (in still air) (see Note 2): DB package | 0.6 W |
| DW package | 1.6 W |
| N package | 1.3 W |
| Storage temperature range, T_{stg} | –65°C to 150°C |

‡ Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. The input and output negative-voltage ratings may be exceeded if the input and output clamp-current ratings are observed.
2. The maximum package power dissipation is calculated using a junction temperature of 150°C and a board trace length of 750 mils, except for the N package, which has a trace length of zero. For more information, refer to the *Package Thermal Considerations* application note in the 1994 *ABT Advanced BiCMOS Technology Data Book*, literature number SCBD002B.

SN54ABT573A, SN74ABT573A

OCTAL TRANSPARENT D-TYPE LATCHES

WITH 3-STATE OUTPUTS

SCBS190B – JANUARY 1991 – MARCH 1996

recommended operating conditions (see Note 3)

| | | | SN54ABT573A | | SN74ABT573A | | UNIT |
|---------------------|------------------------------------|-----------------|-------------|----------|-------------|----------|------|
| | | | MIN | MAX | MIN | MAX | |
| V_{CC} | Supply voltage | | 4.5 | 5.5 | 4.5 | 5.5 | V |
| V_{IH} | High-level input voltage | | 2 | | 2 | | V |
| V_{IL} | Low-level input voltage | | | 0.8 | | 0.8 | V |
| V_I | Input voltage | | 0 | V_{CC} | 0 | V_{CC} | V |
| I_{OH} | High-level output current | | | –24 | | –32 | mA |
| I_{OL} | Low-level output current | | | 48 | | 64 | mA |
| $\Delta t/\Delta v$ | Input transition rise or fall rate | Outputs enabled | | 5 | | 5 | ns/V |
| T_A | Operating free-air temperature | | –55 | 125 | –40 | 85 | °C |

NOTE 3: Unused or floating inputs must be held high or low.

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER | TEST CONDITIONS | | $T_A = 25^\circ\text{C}$ | | | SN54ABT573A | | SN74ABT573A | | UNIT |
|--------------------|--|--------------------------|--------------------------|------|----------------|-------------|----------------|-------------|----------------|---------------|
| | | | MIN | TYP† | MAX | MIN | MAX | MIN | MAX | |
| V_{IK} | $V_{CC} = 4.5\text{ V}$, $I_I = -18\text{ mA}$ | | | | –1.2 | | –1.2 | | –1.2 | V |
| V_{OH} | $V_{CC} = 4.5\text{ V}$, $I_{OH} = -3\text{ mA}$ | | 2.5 | | | 2.5 | | 2.5 | | V |
| | $V_{CC} = 5\text{ V}$, $I_{OH} = -3\text{ mA}$ | | 3 | | | 3 | | 3 | | |
| | $V_{CC} = 4.5\text{ V}$ | $I_{OH} = -24\text{ mA}$ | 2 | | | 2 | | | | |
| | | $I_{OH} = -32\text{ mA}$ | 2* | | | | | 2 | | |
| V_{OL} | $V_{CC} = 4.5\text{ V}$ | $I_{OL} = 48\text{ mA}$ | | | 0.55 | | 0.55 | | | V |
| | | $I_{OL} = 64\text{ mA}$ | | | 0.55* | | | | 0.55 | |
| I_I | $V_{CC} = 5.5\text{ V}$, $V_I = V_{CC}$ or GND | | | | ± 1 | | ± 1 | | ± 1 | μA |
| I_{OZH} | $V_{CC} = 5.5\text{ V}$, $V_O = 2.7\text{ V}$ | | | | 10^\ddagger | | 10^\ddagger | | 10^\ddagger | μA |
| I_{OZL} | $V_{CC} = 5.5\text{ V}$, $V_O = 0.5\text{ V}$ | | | | -10^\ddagger | | -10^\ddagger | | -10^\ddagger | μA |
| I_{off} | $V_{CC} = 0$, V_I or $V_O \leq 4.5\text{ V}$ | | | | ± 100 | | | | ± 100 | μA |
| I_{CEX} | $V_{CC} = 5.5\text{ V}$, $V_O = 5.5\text{ V}$ Outputs high | | | | 50 | | 50 | | 50 | μA |
| I_O^\ddagger | $V_{CC} = 5.5\text{ V}$, $V_O = 2.5\text{ V}$ | | –50 | –100 | –180 | –50 | –180 | –50 | –180 | mA |
| I_{CC} | $V_{CC} = 5.5\text{ V}$, $I_O = 0$, $V_I = V_{CC}$ or GND | Outputs high | | 1 | 250 | | 250 | | 250 | μA |
| | | Outputs low | | 24 | 30 | | 30 | | 30 | mA |
| | | Outputs disabled | | 0.5 | 250 | | 250 | | 250 | μA |
| ΔI_{CC}^\S | $V_{CC} = 5.5\text{ V}$, One input at 3.4 V, Other inputs at V_{CC} or GND | | | | 1.5 | | 1.5 | | 1.5 | mA |
| C_i | $V_I = 2.5\text{ V}$ or 0.5 V | | | | 3.5 | | | | | pF |
| C_o | $V_O = 2.5\text{ V}$ or 0.5 V | | | | 6.5 | | | | | pF |

* On products compliant to MIL-PRF-38535, this parameter does not apply.

† All typical values are at $V_{CC} = 5\text{ V}$.

‡ Not more than one output should be tested at a time, and the duration of the test should not exceed one second.

§ This is the increase in supply current for each input that is at the specified TTL voltage level rather than V_{CC} or GND.

¶ This data sheet limit may vary among suppliers.



SN54ABT573A, SN74ABT573A

OCTAL TRANSPARENT D-TYPE LATCHES

WITH 3-STATE OUTPUTS

SCBS190B – JANUARY 1991 – MARCH 1996

timing requirements over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see Figure 1)

| | | | V _{CC} = 5 V, T _A = 25°C | | SN54ABT573A | | UNIT |
|-----------------|-----------------------------|------|---|-----|-------------|-----|------|
| | | | MIN | MAX | MIN | MAX | |
| t _w | Pulse duration, LE high | | 3.3 | | 3.3 | | ns |
| t _{su} | Setup time, data before LE↓ | High | 1.9 | | 2.5 | | ns |
| | | Low | 1.5 | | 2.5 | | |
| t _h | Hold time, data after LE↓ | | 1 | | 2.5 | | ns |

timing requirements over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see Figure 1)

| | | | V _{CC} = 5 V, T _A = 25°C | | SN74ABT573A | | UNIT |
|-----------------|-----------------------------|------|---|-----|-------------|-----|------|
| | | | MIN | MAX | MIN | MAX | |
| t _w | Pulse duration, LE high | | 3.3 | | 3.3 | | ns |
| t _{su} | Setup time, data before LE↓ | High | 1.9 | | 1.9 | | ns |
| | | Low | 1.5 | | 1.5 | | |
| t _h | Hold time, data after LE↓ | | 1.8† | | 1.8† | | ns |

† This data sheet limit may vary among suppliers.

switching characteristics over recommended ranges of supply voltage and operating free-air temperature, C_L = 50 pF (unless otherwise noted) (see Figure 1)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | V _{CC} = 5 V, T _A = 25°C | | | SN54ABT573A | | UNIT |
|------------------|-----------------|----------------|---|-----|-----|-------------|-----|------|
| | | | MIN | TYP | MAX | MIN | MAX | |
| t _{PLH} | D | Q | 1.9 | 3.2 | 5.4 | 1.4 | 6.4 | ns |
| t _{PHL} | | | 2.2 | 4.2 | 5.7 | 1.6 | 6.7 | |
| t _{PLH} | LE | Q | 2.2 | 4 | 6.1 | 2 | 7.1 | ns |
| t _{PHL} | | | 3.2 | 5.2 | 6.7 | 2.8 | 7.5 | |
| t _{PZH} | \overline{OE} | Q | 1.2 | 3.2 | 4.7 | 0.8 | 6.2 | ns |
| t _{PZL} | | | 2.7 | 4.7 | 6.2 | 2 | 7.2 | |
| t _{PHZ} | \overline{OE} | Q | 2.5 | 4.9 | 6.4 | 2.2 | 7.7 | ns |
| t _{PLZ} | | | 2 | 4.2 | 6 | 1.4 | 7 | |

SN54ABT573A, SN74ABT573A
OCTAL TRANSPARENT D-TYPE LATCHES
WITH 3-STATE OUTPUTS

SCBS190B – JANUARY 1991 – MARCH 1996

switching characteristics over recommended ranges of supply voltage and operating free-air temperature, $C_L = 50$ pF (unless otherwise noted) (see Figure 1)


| PARAMETER | FROM (INPUT) | TO (OUTPUT) | $V_{CC} = 5$ V, $T_A = 25^\circ\text{C}$ | | | SN74ABT573A | | UNIT |
|-----------|-----------------|----------------|---|-----|-----|------------------|------------------|------|
| | | | MIN | TYP | MAX | MIN | MAX | |
| t_{PLH} | D | Q | 1.9 | 3.2 | 5.4 | 1.9 | 5.9 | ns |
| t_{PHL} | | | 2.2 | 4.2 | 5.7 | 2.2 | 6.2 | |
| t_{PLH} | LE | Q | 2.2 | 4 | 6.1 | 2.2 | 6.6 | ns |
| t_{PHL} | | | 3.2 | 5.2 | 6.7 | 3.2 | 7.2 | |
| t_{PZH} | \overline{OE} | Q | 1.2 | 3.2 | 4.7 | 1.2 | 5.2 | ns |
| t_{PZL} | | | 2.5 [†] | 4.7 | 6.2 | 2.5 [†] | 6.7 | |
| t_{PHZ} | \overline{OE} | Q | 2.5 | 4.9 | 6.4 | 2.5 | 7.1 [†] | ns |
| t_{PLZ} | | | 2 | 4.2 | 6 | 2 | 6.5 | |

[†] This data sheet limit may vary among suppliers.

SN54ABT573A, SN74ABT573A OCTAL TRANSPARENT D-TYPE LATCHES WITH 3-STATE OUTPUTS

SCBS190B – JANUARY 1991 – MARCH 1996

PARAMETER MEASUREMENT INFORMATION



NOTES: A. C_L includes probe and jig capacitance.

B. All input pulses are supplied by generators having the following characteristics: $PRR \leq 10 \text{ MHz}$, $Z_O = 50 \Omega$, $t_r \leq 2.5 \text{ ns}$, $t_f \leq 2.5 \text{ ns}$.

C. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.

D. The outputs are measured one at a time with one transition per measurement.

Figure 1. Load Circuit and Voltage Waveforms

IMPORTANT NOTICE

Texas Instruments (TI) reserves the right to make changes to its products or to discontinue any semiconductor product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

TI warrants performance of its semiconductor products and related software to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

Certain applications using semiconductor products may involve potential risks of death, personal injury, or severe property or environmental damage ("Critical Applications").

TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, INTENDED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT APPLICATIONS, DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS.

Inclusion of TI products in such applications is understood to be fully at the risk of the customer. Use of TI products in such applications requires the written approval of an appropriate TI officer. Questions concerning potential risk applications should be directed to TI through a local SC sales office.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards should be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance, customer product design, software performance, or infringement of patents or services described herein. Nor does TI warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used.